

200V-G4 SERIES AIR-COOLED MIDMOUNT™

Take performance
to the next level.



LIMITED WARRANTY

2 YEAR

800 HRS

COMMERCIAL

4 YEAR

800 HRS

RESIDENTIAL

Enjoy comfort, performance and durability with a compact 200V Series mower. An ergonomic design and integrated, multi-point suspension, coupled with the industry's most comfortable seat, lets you stay comfortably in control of every mowing maneuver — even at faster mowing speeds.

200V-G4 models feature G4 Hydro-Gear ZT-4400 transmissions, which are self-contained, heavy-duty commercial transaxles that provide powerful, smooth response. Integrated cooling fans and 1-3/8-inch axles extend service life, and best-in-class transmission fluid change intervals after a 100-hour break-in period reduce costs and maintenance time. Grasshopper's intelligent design transfers more power to the cutting deck to maintain optimum blade tip speed and enhance cut quality in tall or wet grass.

Only two Access-Eze™ lubrication points cut maintenance time up to 95%.

5.5-inch deep decks designed for exceptional durability easily convert from wide-pattern side discharge to optional mulching or vacuum collection. The QuikAjust™ DropPin™ Height Adjustment makes cutting height change fast and simple.

The deep-cushioned, deluxe Premier Comfort seat features a coil-spring suspension and padded lumbar support with sliding 2-inch fore and aft adjustment for all-day comfort. Iso-mounting eliminates vibration before it reaches the seat, and both padded seat and foldable armrests are covered in scuff-resistant, breathable CoolTemp Cordura® fabric, which dissipates heat and won't tear or crack with extended use.

A compact wheelbase provides a great power-to-size ratio for easy transport on trailers and through tighter spaces.

The 6.5 gal/24.6L single-fill fuel tank lowers the center of gravity, providing more traction and stability for an enhanced ride. The standard bumper protects the rear of the mower while preserving easy access to the service shield.

225V-G4

52 61

747 cc, V-twin, OHV Kohler Confidant gasoline engine

226V-G4

52 61

810 cc, V-twin, OHV B&S Commercial turf gasoline engine

227V-G4 EF1

52 61

747 cc, V-twin, Kohler Confidant Delphi-based® closed-loop, Electronic Fuel Injection gasoline engine

Increase your productivity with speeds up to 9.0 mph and 5.00 acres per hour with a 61-inch cutting deck.*

9 MPH
5.00
ACRES PER HOUR*

► DuraMax® deck

OPTIONS

- » Quik-D-Tatch® PowerVac™ Collection Systems
- » 4X Rear Discharge™ decks
- » Down Discharge™ mulching packages
- » Side discharge control kit
- » Foot pedal extension kit for QuikAjust™ DropPin™ height adjustment
- » TrimAide™ roller kit (52-inch decks only)
- » Speed-Trimming™ heavy-duty roller kit (61-inch decks)
- » Air Dam kit
- » LED work lights — plug-in ready
- » Yellow beacon light
- » Sunshade Canopy — vinyl or aluminum
- » Custom Cordura® weather cover
- » GrassMax™ blade options
- » Heavy-duty, grass-grooming stripping kit
- » QuikAjust Tilt™ steering levers with "no tools" 9-inch comfort range
- » Wide seat conversion kit
- » Extended levers for taller operators
- » Foldable ROPS with adjustable seat belt
- » DuraFlex™ suspension forks
- » Edge-EZE™ edger
- » Tine-Rake™ Dethatcher

* Results may vary based on conditions. See grasshoppermower.com/acres for details.

Models may be shown with optional equipment.

AIR-COOLED 200V-G4 SERIES-SPECIFICATIONS

MODEL – CUTTING WIDTH

	225V- G4 52	225V- G4 61	226V- G4 52	226V- G4 61	227V- G4 52	227V- G4 61
--	----------------	----------------	----------------	----------------	----------------	----------------

ENGINE

Type/Displacement/Cylinders

Kohler Confidant gasoline/45.6 cu. in. (747 cc)/V-twin	•	•				
B&S Vanguard – gasoline/49.4 cu. in. (810cc)/v-twin			•	•		
Kohler Confidant, Delphi®-based, closed-loop gasoline Electronic Fuel Injection (EFI)/45.6 cu. in. (747 cc)/V-twin					•	•

Lubrication System

Pressure Lube, Filter

Crankshaft

Vertical

Cooling System

Air

Fuel / Capacity

Gasoline - unleaded / 6.5 U.S. Gal (24.6 L)	•	•	•	•	•	•
---	---	---	---	---	---	---

Air Cleaner

Heavy-duty cyclonic air filter with QuadClean™ multi-stage air filtration

Remote-mounted, centrifugal multi-stage air cleaner with advanced debris management

Muffler

Ultra-quiet, single, industrial type

MOWING DECKS

Construction (Robotic-welded steel)

Double-layered 10-gauge plus 7-gauge formed steel laminate spindle plane 0.313 in. (7.95 mm) thick – more than 25% thicker than 0.25 in. (6.35 mm) – with 7-gauge skirts for geometric strength.

Spindle plane is 0.9 in. (22.86 mm) thick in stress zones. Anvil-edge design with 0.5 in. (12.7 mm) reinforcement on front edge of deck.

Blades (ADI MARBAIN®, 1/4-in.)

(3) 18 in. (45.7 cm)	•		•		•	
(3) 21 in. (53.3 cm)		•		•	•	•

Spindle Assemblies

Sentry™ Spindle System, 2.5 cm (approx. 1 in.) O.D. shaft. Spindle head designed to eliminate fiber wrap. Double bearings, non-greaseable.

Spindle Housing

8-in. (20.3 cm)-diameter machined aluminum housing with 6-bolt pattern.

Spindle Cones

Spindle cones shield housing and lower bearings from fiber wrap and dirt ingestion.

QuikAjust™ DropPin™ Height Adjustment

Foot-controlled height adjustment pedal with pin

Cutting Height Range

1.0 – 5.0 in. (2.5 – 12.7 cm) in 1/4-inch increments

Blade Drive

Belt drive with single Kevlar V-belt & idler arm tensioning

STARTER & ELECTRICAL SYSTEM

Maintenance-Free Battery/Charging Capacity/Starter

12 Volt/15 amp/solenoid shift	•	•			•	•
12 Volt/16 amp/solenoid shift			•	•		

Ignition

Breakerless

Interlock System

Prevents engine start when PTO clutch is engaged or steering levers are in drive position. Allows operator dismount without engine shutdown only when PTO is disengaged and steering levers are locked in neutral.

ULTIMATE OPERATOR STATION™

Premier Comfort Seat

Iso-mounted, high-back, deep-cushioned, foam-padded Cordura®-covered, padded arms/backrest with lumbar support, coil-spring suspension and embroidered Grasshopper logo on seat back. Adjustable fore and aft.

Suspension

Roomy, iso-mounted footrest with Shock Impact Reduction System™ (SIRS™).

MODEL – CUTTING WIDTH

	225V- G4 52	225V- G4 61	226V- G4 52	226V- G4 61	227V- G4 52	227V- G4 61
--	----------------	----------------	----------------	----------------	----------------	----------------

Console-Mounted Instruments

Low engine oil pressure, digital hour meter, parking brake indicator light, ignition switch, choke & push/pull PTO switch.

Low engine oil pressure, digital hour meter, engine code light and parking brake warning lights, ignition & push/pull PTO switches.

Work Lights (Pre-wired)

LED (optional)

TRANSMISSION & STEERING

Type

Heavy-duty Hydro-Gear ZT-4400 hydrostatic transmissions with cooling fans. Integrated transaxles with 12cc piston pumps and 16cc piston motors, gear reduction, internal disc brakes, and 1-3/8 inch axles.

Filtration/Hydro Fluid

Self-contained fluid and internal filtration / CoolTemp Hydro-Max™ fluid withstands high and low temperature extremes for extended service intervals after 100-hour break in oil change.

Speed

0 – 9.0 mph (0 – 14.5 kph) forward	•	•	•	•	•	•
0 – 6.0 mph (0 – 9.7 kph) reverse						

Turning Radius

True zero degree, turns within own length with counter-rotating, independently powered drive wheels.

Steering

One- or two-hand operation with adjustable Hydra-Smooth™ dual levers that automatically return to neutral from either forward or reverse position.

Brakes

Dynamic braking through hydrostatic transmission

Parking Brake

Internal disc brake in transmission.

TIRE SIZES

Drive Wheels – Standard (5-bolt pattern)

23x10.50x12 turf type, 4-ply rated	•	•	•	•	•	•
------------------------------------	---	---	---	---	---	---

Front Casters

13x6.5x6 rib tread, pneumatic with double-sealed bearings

DIMENSIONS (Mower & Deck)

Mulch Width/Length (Add 1.5 in. (3.8 cm) to width for side discharge with deflector raised. Add 12.0 in. (30.5 cm) to width for side discharge with deflector.)

53.5 in. (135.9 cm)/76.0 in. (193.0 cm)	•		•		•	
62.5 in. (158.8 cm)/79.0 in. (200.7 cm)		•		•	•	•

Height (Seat back)

46.0 in. (116.8 cm)						
---------------------	--	--	--	--	--	--

Height (Seat cushion)

30.0 in. (76.2 cm)						
--------------------	--	--	--	--	--	--

Height (ROPS)

68.0 in. (172.7 cm)						
---------------------	--	--	--	--	--	--

Drive Tire Track Width (outside edge to outside edge)

50.0 in. (127.0 cm)						
---------------------	--	--	--	--	--	--

WEIGHT

Uncrated (Mower & Deck)

960 lbs. (435.4 kg)			•			
980 lbs. (444.5 kg)	•					
1030 lbs. (467.2 kg)				•		
1050 lbs. (476.3 kg)		•				•

Mulching Package (Package includes high-low mulching blades.)

29 lbs. (13.2 kg)	•		•		•	
36 lbs. (16.3 kg)		•		•		•

• Standard ○ Option

For a complete list of trademarks/registered trademarks, visit grasshoppermower.com/legal.

Litho in U.S.A. © 2019 The Grasshopper Company



The Grasshopper Company • 105 Old U.S. Highway 81
P.O. Box 637 • Moundridge, KS • 67107 U.S.A.
T: 620-345-8621 • grasshoppermower.com

